



DALIAN LUYANG TECHNOLOGY DEVELOPMENT CO., LTD.
PEEK BAR SPECIFICATIONS (Unit: mm)

No.	Bar Dia.	D.Tol.	R.Tol.	kg/m (kg/m)	No.	Bar Dia.	D.Tol.	R.Tol.	kg/m (kg/m)
1	5	+0.1/+0.6	0.1	0.03	29	72	+0.6/+2.5	0.35	5.44
					30	75			5.99
					31	78			6.37
2	6	+0.1/+0.6	0.1	0.05	32	80	+0.6/+3	0.35	7.08
3	8	+0.1/+0.8	0.2	0.06	33	85			7.67
4	10			0.11	34	90			8.55
5	12	+0.2/+1.2	0.3	0.16	35	93			9.02
6	13			0.20	36	95			9.43
7	15			0.25	37	100			10.73
8	16			0.27	38	105			11.47
9	18			0.36	39	110			12.93
10	20			0.45	40	115			13.53
11	22	+0.3/+1.5	0.3	0.53	41	120	+0.6/+3.5	0.35	15.44
12	25			0.67	42	125		0.4	16.18
13	26			0.73	43	130			20.08
14	28			0.84	44	140			20.55
15	30			0.94	45	150	+1.1/+5.0	0.4	23.81
16	32			1.07	46	160		0.5	26.85
17	33	1.19	47	165	29.01				
18	35	+0.3/+2.0	0.3	1.35	48	170			30.22
19	38			1.52	49	180			33.99
20	40			1.71	50	190			37.86
21	42			1.91	51	200		1.00	43.26
22	45			2.13	52	210			46.08
23	50			2.66	53	220	+1.3/+6.0	1.00	50.79
24	53			2.95	54	230			55.56
25	55			+0.3/+2.5	0.3	3.14	55	250	+1.5/+6.5
26	60	3.95	56			260	71.12		
27	65	4.37	57			300	+2.0/+15.0	2.0	92.10
28	70	+0.6/+2.5	0.35	5.51					